

profilan®-cover



D Lösemittelhaltiger, hochwetterfester, hochdeckender, leicht zu verarbeitender Allwetterlack mit schneller Trocknung für Holz im Innen- und Außenbereich.

Anwendungsgebiete:

profilan®-cover ist eine Grund-, Zwischen- und Endbeschichtung für Holz und Holzbauteile.

Eigenschaften:

- Schnelle Trocknung
- Hohe Füllkraft
- Blockfest
- Strapazierfähig
- Ventilierend/wasserdampfdurchlässig
- Beste Kantenabdeckung
- Hohes Deckvermögen
- Lange Haltbarkeit
- Holzfarbstoffe werden nicht angelöst (dadurch keine Gelbfärbung)

Verarbeitung: 

Verbrauch: 140 – 160 ml/m²; in 2-3 Arbeitsgängen.

Gebindegrößen: 0,75 l / 2,5 l.

GB Solvent-based, highly weather-resistant, highly opaque, quick drying all-weather lacquer, ease of application for wood used in- and outdoors.

Applications:

profilan®-cover is to be used as a primer, intermediate and finish coat for timber and timber elements.

Properties:


- Fast drying
- High filling characteristics
- Block resistant
- Hard-wearing
- Ventilating/water vapour permeable
- Optimal edge coverage
- High covering power
- Long shelf life
- Natural wood pigments are not dissolved, so no yellowing effect

Application method: 

Application rate: 140 – 160 ml/m²; in 2-3 coats.

Pack sizes: 0.75 l / 2.5 l.

RÜTGERS Organics GmbH
Oppauer Straße 43
D-68305 Mannheim
Tel.: +49 (0)621 7654-247
Fax: +49 (0)621 7654-449
info@impra.de
www.impra.de



W601396/08.2015



we care for wood

Deckende Farbtöne

Opaque Colours

profilan®
opac | cover



profilan®



profilan®-opac

D Wasserbasierender, hochwetterfester Allwetterlack mit vorbeugendem Filmschutz gegen Schimmel und Algen für Holz im Innen- und Außenbereich.

Anwendungsgebiete:

profilan®-opac ist für Hölzer wie z.B. Fachwerk, Balkone, Holzfassaden, Fenster und Türen, Gartenhäuser u.a. nach Vorbehandlung auch auf Mauerwerk, Beton, Putz, Hart-PVC, Zink und verzinktem Stahl einsetzbar.

Eigenschaften:

- Hochdeckend und feuchtigkeitsregulierend
- Sehr gute Haftung an Altanstrichen
- Wirksamkeit gegen Schimmel und Algen
- Eignungsnachweis nach DIN EN 927-2
- Blockfest

Verarbeitung:   

Verbrauch: 100 – 180 ml/m²; in 2 Arbeitsgängen.

Gebindegrößen: 0,75 l / 2,5 l / 10 l.

GB Water-based, highly weather-resistant, all-weather lacquer with protective film against mould and algae for use on both interior and exterior wood.

Applications:

profilan®-opac is to be used on timber elements such as framework, balconies, wooden facades, windows and doors, summerhouses, etc. After appropriate pre-treatment also suitable for treating brickwork, concrete, plaster, hard PVC, zinc and galvanised steel.

Properties:

- High covering power and moisture regulation
- Very good adhesion on existing paintwork
- Effective against mould and algae
- Suitability certified according to DIN EN 927-2
- Block resistant

Application method:   

Application rate: 100 – 180 ml/m²; in 2 coats.

Pack sizes: 0.75 l / 2.5 l / 10 l.

Farbkollektion

9010
Birkenweiß
Birch white



7135

Achat
Agate



1102

Sahara
Sahara



3101

Signalrot
Red



3111

Fachwerkrot
Crimson



8117

Balkenbraun
Chocolate



9105

Tiefschwarz
Black



RAL 9007*

Graualuminium
Grey aluminium



7140

Lichtgrau
Opal white



7130

Rauchgrau
Smoke grey



1117

Ocker
Yellow ochre



3140

Schwedenrot
Sweden red



8108

Borkenbraun
Bark brown



6105

Tannengrün
Fir green



RAL 9006*

Weißaluminium
White aluminium



Wir mischen auch Sonderfarbtöne ganz nach Ihren Wünschen (Abmischung nach RAL- und NCS-Farbkarte).

Also available in special color shades in compliance with your requirements (according to RAL- and NCS colour cards).

* Nur für profilan®-opac. profilan®-opac only.