Revision: 12.04.2024

Safety data sheet according to Regulation (EC) No 1907/2006, Article 31

Printing date 16.04.2024 Version

Version number 41 (replaces version 40)

SECTION 1: Identification of the substance/mixture and of the company/undertaking

• 1.1 Product identifier

Trade name: profilan-color 0000 farblos

Article number: W716101UFI: AQ00-70AS-800U-470W

• 1.2 Relevant identified uses of the substance or mixture and uses advised against

No further relevant information available.

· Application of the substance / the mixture Coating

• 1.3 Details of the supplier of the safety data sheet

• Manufacturer/Supplier: RÜTGERS Organics GmbH

Oppauer Straße 43 D-68305 Mannheim Tel.: **49-621-76540 US: 1-980-253-8880 Fax: **49-621-7654446

e-mail: SDB.rog@ruetgers-organics.de

• Informing department: see: Heading 16 (Contact)

• 1.4 Emergency telephone number: see: Manufacturer/Supplier

SECTION 2: Hazards identification

- 2.1 Classification of the substance or mixture
- Classification according to Regulation (EC) No 1272/2008



Eye Irrit. 2 H319 Causes serious eye irritation.

- · 2.2 Label elements
- · Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the GB CLP regulation.

Hazard pictograms



· Signal word Warning

· Hazard statements

H319 Causes serious eye irritation.

Precautionary statements

P264 Wash thoroughly after handling.
P280 Wear eye protection / face protection.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact

lenses, if present and easy to do. Continue rinsing.

P337+P313 If eye irritation persists: Get medical advice/attention.

Additional information:

Contains cobalt(II) 2-ethylhexanoate, 3-lodo-2-propynylbutylcarbamate. May produce an allergic reaction.

- · 2.3 Other hazards
- · Results of PBT and vPvB assessment
- PBT: Not applicable.

(Contd. on page 2)

Printing date 16.04.2024 Version number 41 (replaces version 40) Revision: 12.04.2024

Trade name: profilan-color 0000 farblos

• vPvB: Not applicable.

(Contd. of page 1)

SECTION 3: Composition/information on ingredients

- · 3.2 Mixtures
- Description: Mixture consisting of the following components.

CAS: 64742-48-9	Naphtha (petroleum), hydrotreated heavy	25-50%
	♦ Asp. Tox. 1, H304; ♦ Acute Tox. 4, H332	20 0070
	Poly(oxy-1,2-ethandiyl), alpha-(2propylheptyl)-omega- hydroxy-polymer	<2%
	Eye Dam. 1, H318; (1) Acute Tox. 4, H302	
CAS: 2457-01-4	Barium bis(2-ethylhexanoat)	0-<2%
EINECS: 219-535-8 Index number: 056-002-00-7	♠ Acute Tox. 4, H302; Acute Tox. 4, H332	
CAS: 85203-81-2	Hexanoic Acid, 2-Ethyl-, Zinc Salt, Basic	0-<2%
EINECS: 286-272-3	Repr. 2, H361d; Eye Irrit. 2, H319; Aquatic Chronic 3, H412	
CAS: 34590-94-8 EINECS: 252-104-2	Dipropylene glycol monomethyl ether substance with a Community workplace exposure limit	0-<0.5%
CAS: 872-50-4	N-methyl-2-pyrrolidone	<0.5%
EINECS: 212-828-1 Index number: 606-021-00-7	Acute Tox. 3, H331; Repr. 1B, H360D; Skin Irrit. 2, H315; Eye Irrit. 2, H319; STOT SE 3, H335 Specific concentration limit: STOT SE 3; H335: C ≥ 10 %	
CAS: 136-52-7	cobalt(II) 2-ethylhexanoate	<0.5%
EINECS: 205-250-6	Repr. 2, H361f; Aquatic Acute 1, H400; Acute Tox. 4, H302; Eye Irrit. 2, H319; Skin Sens. 1, H317; Aquatic Chronic 3, H412	
CAS: 55406-53-6	3-lodo-2-propynylbutylcarbamate	<0.5%
EINECS: 259-627-5 Index number: 616-212-00-7	Acute Tox. 3, H331; STOT RE 1, H372; Eye Dam. 1, H318; Aquatic Acute 1, H400 (M=10); Aquatic Chronic 1, H410 (M=1); Acute Tox. 4, H302; Skin Sens. 1, H317	
	Aliphatische Carbonsäure & Repr. 2, H361d	0-<0.5%

· SVHC

872-50-4 N-methyl-2-pyrrolidone

• Additional information For the wording of the listed hazard phrases refer to section 16.

SECTION 4: First aid measures

- 4.1 Description of first aid measures
- After inhalation Supply fresh air; consult doctor in case of symptoms.
- After skin contact Instantly wash with water and soap and rinse thoroughly.
- After eye contact Rinse opened eye for several minutes under running water.
- After swallowing In case of persistent symptoms consult doctor.
- 4.2 Most important symptoms and effects, both acute and delayed No further relevant information available.
- 4.3 Indication of any immediate medical attention and special treatment needed No further relevant information available.

Printing date 16.04.2024 Version number 41 (replaces version 40) Revision: 12.04.2024

Trade name: profilan-color 0000 farblos

(Contd. of page 2)

SECTION 5: Firefighting measures

- 5.1 Extinguishing media
- · Suitable extinguishing agents

CO2, extinguishing powder or water jet. Fight larger fires with water jet or alcohol-resistant foam.

• 5.2 Special hazards arising from the substance or mixture No further relevant information available.

- 5.3 Advice for firefighters
- Protective equipment: No special measures required.

SECTION 6: Accidental release measures

- 6.1 Personal precautions, protective equipment and emergency procedures Wear protective equipment. Keep unprotected persons away.
- 6.2 Environmental precautions: No special measures required.
- 6.3 Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

· 6.4 Reference to other sections

See Section 7 for information on safe handling

See Section 8 for information on personal protection equipment.

See Section 13 for information on disposal.

SECTION 7: Handling and storage

- 7.1 Precautions for safe handling No special precautions necessary if used correctly.
- Information about protection against explosions and fires: No special measures required.
- 7.2 Conditions for safe storage, including any incompatibilities
- Storage
- Requirements to be met by storerooms and containers: No special requirements.
- Information about storage in one common storage facility: Not required.
- Further information about storage conditions: None.
- 7.3 Specific end use(s) No further relevant information available.

SECTION 8: Exposure controls/personal protection

- 8.1 Control parameters
- · Components with limit values that require monitoring at the workplace:

The product does not contain any relevant quantities of materials with critical values that have to be monitored at the workplace.

34590-94-8 Dipropylene glycol monomethyl ether

WEL Long-term value: 308 mg/m³, 50 ppm

872-50-4 N-methyl-2-pyrrolidone

WEL Short-term value: 80 mg/m³, 20 ppm Long-term value: 40 mg/m³, 10 ppm Sk

136-52-7 cobalt(II) 2-ethylhexanoate

WEL Long-term value: 0.1 mg/m³ as Co; Carc, Sen

- Additional information: The lists that were valid during the compilation were used as basis.
- · 8.2 Exposure controls
- Appropriate engineering controls

Provide adequate general and local exhaust ventilation. Ensure the ventilation system is regularly maintained and tested. Good general ventilation should be adequate to control

(Contd. on page 4)

Printing date 16.04.2024 Version number 41 (replaces version 40) Revision: 12.04.2024

Trade name: profilan-color 0000 farblos

(Contd. of page 3)

worker exposure to airborne contaminants. Observe any occupational exposure limits for the product or ingredients

- · Individual protection measures, such as personal protective equipment
- · General protective and hygienic measures

Wash hands thoroughly after handling. Wash at the end of each work shift and before eating, smoking and using the toilet. Do not eat, drink or smoke when using this product.

- Breathing equipment: Not required.
- Hand protection

The glove material has to be impermeable and resistant to the product.

No recommendation to the specific glove material can be given for the product. Please refer to glove manufacurer for siutability.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

- Material of gloves Please refer to the above paragraph.
- · Penetration time of glove material

Please refer to the glove manufacturer and the information in the paragraphs above.

- Eye/face protection Safety glasses recommended during refilling.
- · Body protection:

Protective work clothing. Wear appropriate clothing to prevent any possibility of skin contact.

SECTION 9: Physical and chemical properties

• 9.1 Information on basic physical and chemical properties

· General Information

• Physical state Fluid

• Colour: According to product specification

Odour: Characteristic
 Odour threshold: Not determined.
 Melting point/freezing point: Not determined

• Boiling point or initial boiling point and

boiling range 100 °C

• Flammability Not applicable.

· Lower and upper explosion limit

Lower: 0.6 Vol %
Upper: 6 Vol %
Flash point: 68 °C
Auto-ignition temperature: >200 °C

• Decomposition temperature: Not determined.

• pH at 20 °C 6-8

Viscosity:

• Kinematic viscosity at 20 °C 40 s (DIN 53211/4) • dynamic: Not determined.

• Solubility

• Water: Not miscible or difficult to mix

Partition coefficient n-octanol/water (log

value) Not determined.

• Vapour pressure at 20 °C: 23 hPa

· Density and/or relative density

Density at 20 °C
 Relative density
 Vapour density
 O.93 g/cm³
 Not determined.
 Not determined.

- 9.2 Other information
- Appearance:

• Form: Fluid

(Contd. on page 5)

Printing date 16.04.2024 Version number 41 (replaces version 40) Revision: 12.04.2024

Trade name: profilan-color 0000 farblos

(Contd. of page 4)

• Important information on protection of health

and environment, and on safety.

Self-inflammability: Product is not selfigniting.
 Explosive properties: Product is not explosive.

· Solvent content:

• Organic solvents: >35.2-<36.5 % • Water: 20.0 %

· Change in condition

• Evaporation rate Not determined.

Information with regard to physical hazard classes

 Explosives Void Void · Flammable gases Void Aerosols Void Oxidising gases · Gases under pressure Void Flammable liquids Void Flammable solids Void · Self-reactive substances and mixtures Void Void Pyrophoric liquids Void Pyrophoric solids Void Self-heating substances and mixtures Substances and mixtures, which emit flammable gases in contact with water

flammable gases in contact with water

Oxidising liquids

Oxidising solids

Organic peroxides

Corrosive to metals

Desensitised explosives

Void

SECTION 10: Stability and reactivity

- 10.1 Reactivity No further relevant information available.
- 10.2 Chemical stability
- Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- 10.3 Possibility of hazardous reactions No dangerous reactions known
- 10.4 Conditions to avoid No further relevant information available.
- 10.5 Incompatible materials: No further relevant information available.
- 10.6 Hazardous decomposition products: No dangerous decomposition products known

SECTION 11: Toxicological information

- 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008
- · Acute toxicity Based on available data, the classification criteria are not met.

• LD/LC50 values that are relevant for classification:

64742-48-9 Naphtha (petroleum), hydrotreated heavy

Oral LD50 >5,000 mg/kg (Rattus norvegicus (Ratte))
Dermal LD50 >3,160 mg/kg (Oryctolagus cuniculus (eur. Kaninchen))
Inhalative LC50/4 h >12 mg/l (Rattus norvegicus (Ratte))

• Serious eye damage/irritation Causes serious eye irritation.

(Contd. on page 6)

Printing date 16.04.2024 Version number 41 (replaces version 40) Revision: 12.04.2024

Trade name: profilan-color 0000 farblos

11.2 Information on other hazards

(Contd. of page 5)

- Endocrine disrupting properties

None of the ingredients is listed.

SECTION 12: Ecological information

- 12.1 Toxicity
- Aquatic toxicity: No further relevant information available.
- 12.2 Persistence and degradability No further relevant information available.
- 12.3 Bioaccumulative potential No further relevant information available.
- 12.4 Mobility in soil No further relevant information available.
- 12.5 Results of PBT and vPvB assessment
- PBT: Not applicable.
- · vPvB: Not applicable.
- 12.6 Endocrine disrupting properties

The product does not contain substances with endocrine disrupting properties.

- 12.7 Other adverse effects
- Additional ecological information:
- · General notes:

Water hazard class 2 (German Regulation) (Self-assessment): hazardous for water.

Do not allow product to reach ground water, water bodies or sewage system.

Danger to drinking water if even small quantities leak into soil.

SECTION 13: Disposal considerations

- 13.1 Waste treatment methods
- Recommendation

Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

• 14.1 UN number or ID number • ADR, ADN, IMDG, IATA	Void	
• 14.2 UN proper shipping name • ADR, ADN, IMDG, IATA	Void	
• 14.3 Transport hazard class(es)		
• ADR, ADN, IMDG, IATA • Class	Void	
• 14.4 Packing group • ADR, IMDG, IATA	Void	
• 14.5 Environmental hazards: • Marine pollutant:	No	
• 14.6 Special precautions for user	Not applicable.	
• 14.7 Maritime transport in bulk accordi IMO instruments	ng to Not applicable.	
• UN "Model Regulation":	Void	

Printing date 16.04.2024 Version number 41 (replaces version 40) Revision: 12.04.2024

Trade name: profilan-color 0000 farblos

(Contd. of page 6)

SECTION 15: Regulatory information

- 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture
- Poisons Act
- Regulated explosives precursors

None of the ingredients is listed.

Regulated poisons

None of the ingredients is listed.

Reportable explosives precursors

None of the ingredients is listed.

Reportable poisons

None of the ingredients is listed.

- Directive 2012/18/EU
- Named dangerous substances ANNEX I None of the ingredients is listed.
- National regulations
- Substances of very high concern (SVHC) according to UK REACH

872-50-4 N-methyl-2-pyrrolidone

• 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

These data are based on our present knowledge. However, they shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship. It is the responsibility of the user to assure himself that the information provided with this material safty data sheet is complete and applicable for his utilization of the product.

· Relevant phrases

- H302 Harmful if swallowed.
- H304 May be fatal if swallowed and enters airways.
- H315 Causes skin irritation.
- H317 May cause an allergic skin reaction. H318 Causes serious eye damage.
- H319 Causes serious eye irritation.
- H331 Toxic if inhaled.
- H332 Harmful if inhaled.
- H335 May cause respiratory irritation.
- H360D May damage the unborn child.
- H361d Suspected of damaging the unborn child.
- H361f Suspected of damaging fertility.
- H372 Causes damage to organs through prolonged or repeated exposure.
- H400 Very toxic to aquatic life.
- H410 Very toxic to aquatic life with long lasting effects.
- H412 Harmful to aquatic life with long lasting effects.
- · Department issuing data specification sheet: Product safety department, Mannheim
- Contact:

RÜTGERS Organics

Product Safety

Tel. **49 / 621 7654 247

Abbreviations and acronyms:

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)

ICAO: International Civil Aviation Organisation

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)

(Contd. on page 8)

(Contd. of page 7)

Safety data sheet according to Regulation (EC) No 1907/2006, Article 31

Printing date 16.04.2024 Version number 41 (replaces version 40) Revision: 12.04.2024

Trade name: profilan-color 0000 farblos

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic vPvB: very Persistent and very Bioaccumulative Acute Tox. 3: Acute toxicity – Category 3 Acute Tox. 4: Acute toxicity – Category 4

Skin Irrit. 2: Skin corrosion/irritation - Category 2

Eye Dam. 1: Serious eye damage/eye irritation - Category 1 Eye Irrit. 2: Serious eye damage/eye irritation – Category 2

Skin Sens. 1: Skin sensitisation - Category 1

Repr. 1B: Reproductive toxicity - Category 1B

Repr. 2: Reproductive toxicity – Category 2 Repr. 2: Reproductive toxicity – Category 2

STOT SE 3: Specific target organ toxicity (single exposure) - Category 3 STOT RE 1: Specific target organ toxicity (repeated exposure) - Category 1

Asp. Tox. 1: Aspiration hazard – Category 1

Aquatic Acute 1: Hazardous to the aquatic environment - acute aquatic hazard - Category 1

Aquatic Chronic 1: Hazardous to the aquatic environment - long-term aquatic hazard - Category 1

Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard - Category 3

• * Data compared to the previous version altered.